## **How To Order Part Number**

## M Series With cable molded F MA 80 F Α 03 ST 03 С В 25 **SERIES** WIRE SECTION $25 = 0.25 \text{mm}^2$ $34 = 0.34 \text{mm}^2$ SIZE $50 = 0.50 \text{mm}^2$ 05 = M508 = M809 = M9**CABLE COLOR** 10 = M10B = Black 12 = M12G = Gray16 = M16O = Orange 20 = M20Y = Yellow 24 = RD24**TYPE CABLE SHEATH** F = Female C = PVCM = Male R = PURFS =Female shield MS = Male shield LN = Female with LED NPN LP = Female with LED PNP FR = Female reversed polarity MR = Male reversed polarity CABLE LENGTH 03 = 0.3m**CODING** 10 = 1m A = A Coding 20 = 2mB = B Coding 100 = 10mC = C Coding D = D Coding S = S Coding X = X Coding **INSERT DEGREE** T = T Coding ST = Straight RA = Right angled **LOCKING SYSTEM** F = Fixed screw I = Snap inP = Plastic fix screw Q = Quick-lock HD = Hex Die-cast screw **POLES** 03 = 3 Poles 04 = 4 Poles05 = 5 Poles 08 = 8 Poles..... 3+5 = 3+5 Poles