


Multi-conductor Cable



UL20276 Multi-Conductor Cable



Product Description

- Tinned, annealed, stranded copper conductor.
- First type core: PP or PE insulation
- Second type core: sr-PVC insulation
- Cores cabled under aluminum mylar shield
- Tinned or BARE copper drain wire.
- Tinned or bare copper braid shield.
- PVC jacket.
- Rated temperature: 80°C, Rated voltage: 30Volts
- Pass UL VW-1&CSA FT1 vertical flame test

Detailed Specifications

- For internal wiring or external wiring of class 2 systems equipment and electronic equipment

Technical Data

UL Style& CSA Type	Cores	Conductor		Insulation Thickness	Nom. Dia	Drain Wire	Overall Shield		Jacket Thickness	Overall Diameter	Conductor Resistance at 20°C
		Gauge	No./OD				Material	Spiral/Braids			
		AWG	No./mm				mm	Coverage			Ω/KM
UL20276CSA (Stranded)	3P	26	7/0.16	0.26	1.00	/	PAPER	80.00%	1.05	6.40	150.00
	1C	26	7/0.16	0.26	1.00	/	PAPER	80.00%	1.05	6.40	150.00
	3P	28	7/0.127	0.12	0.65	7/0.16	AL	85.00%	0.56	4.70	239.00
	9C	28	7/0.127	0.12	0.65	7/0.16	AL	85.00%	0.56	4.70	239.00
	12P	28	7/0.127	0.12	0.65	7/0.20	AL	85.00%	1.00	6.70	239.00
	1C	28	7/0.127	0.12	0.65	7/0.20	AL	85.00%	1.00	6.70	239.00
	6P	28	7/0.127	0.12	0.65	7/0.127	PET	70.00%	0.70	4.70	239.00
	7P	28	7/0.127	0.12	0.65	/	PAPER	85.00%	0.95	5.30	239.00
	8P	28	7/0.10	0.12	0.65	7/0.127	PET	85.00%	0.70	5.00	239.00
	13P	28	7/0.127	0.12	0.65	7/0.20	AL	85.00%	0.92	7.00	239.00
	18P	28	7/0.127	0.12	0.65	/	AL	85.00%	0.76	7.40	239.00
	19P	30	7/0.10	0.15	0.60	7/0.127	AL	85.00%	1.28	8.50	381.00
	25P	30	7/0.10	0.15	0.60	7/0.127	AL	85.00%	1.39	9.50	381.00
	25P	28	7/0.127	0.12	0.65	/	AL	85.00%	0.72	8.20	239.00