


Multi-conductor Cable



UL2725/UL2785 Multi-conductor Shielded Cable



Product Description

- Tinned, annealed, stranded or solid copper conductor.
- SR-PVC insulation or PVC insulation
- PVC jacket
- Filler and paper separator applied.
- Rated temperature: 2725 60°C, 2785 60°C
- Rated voltage: 2725 30Volts, 2785 300Volts
- Pass UL VW-1&CSA FT1 vertical flame test

Applications

- For use in recording studios, sound systems and electronic circuits

Technical Data

UL Style& CSA Type	Cores	Conductor		Insulation Thickness	Nom. Dia	Jacket Thickness	Overall Diameter	Conductor Resistance at 20°C
		Gauge	No./OD					
		AWG	No./mm					
UL2725 UL2785 CSA (Stranded)	3C	30	7/0.10	0.18	0.70	0.51	3.40	381.00
	4C	30	7/0.10	0.18	0.70	0.51	3.40	381.00
	6C	30	7/0.10	0.18	0.70	0.51	3.60	381.00
	8C	30	7/0.10	0.18	0.70	0.51	3.80	381.00
	9C	30	7/0.10	0.18	0.70	0.51	4.00	381.00
UL2725 UL2785 CSA (Stranded)	3C	28	7/0.127	0.18	0.80	0.51	3.40	239.00
	4C	28	7/0.127	0.18	0.80	0.51	3.40	239.00
	6C	28	7/0.127	0.18	0.80	0.51	3.60	239.00
	8C	28	7/0.127	0.18	0.80	0.51	3.80	239.00
	9C	28	7/0.127	0.18	0.80	0.51	4.00	239.00

PVC Jacket cable