



Multi-conductor Cable



UL2835 Multi-conductor Shielded Cable



Product Description

- Tinned, annealed, stranded copper conductor or tinsel conductor.
- PVC or PE or PP insulation.
- Cores cabled under aluminum mylar shield.
- Tinned stranded copper drain wire.
- Tinned or bare copper braid shield.
- PVC jacket or Non-migration jacket available.
- Rated temperature: 60°C. Rated voltage: 30Volts
- Pass UL VW-1&CSA FT1 vertical flame test

Applications

- For internal wiring in class 2 circuits of electronic equipment or TV game machine data transmission

Technical Data

UL Style& CSA Type	Cores	Conductor		Insulation Thickness	Nom. Dia	Drain Wire	Overall shield		Jacket Thickness	Overall Diameter	Conductor Resistance at 20°C
		Gauge	No./OD				Material	Spiral/Braids			
		AWG	No./mm				mm	NO./No.mm			
UL2661CSA (Stranded)	4C	28	7/0.127	0.22	0.82	/	AL	57/0.1	1.00	4.30	239.00
	4C	22	17/0.16	0.22	1.20	17/0.16	AL	/	0.45	4.00	59.40
	5C	28	19/0.08	0.2	0.80	/	PAPER	16/6/0.12	0.88	4.80	239.00
	6C	28	7/0.127	0.22	0.82	/	AL	79/0.1	0.68	4.30	239.00
	7C	28	7/0.127	0.26	0.90	7/0.127	/	75/0.12	0.90	5.00	239.00
	7C	32	TINSEL	0.22	1.00	7/0.127	/	16/7/0.1	0.75	5.20	563.00
	8C	28	19/0.08	0.23	0.86	/	PAPER	16/8/0.1	0.75	4.80	239.00
	9C	28	7/0.127	0.22	0.82	/	PAPER	81/0.12	0.75	4.90	239.00
	10C	28	7/0.127	0.26	0.90	7/0.127	AL	/	0.6	5.00	239.00

PVC Jacket cable