



Multi-conductor Cable



UL20236 Multi-Conductor Shielded Cable



Product Description

- Tinned, annealed, stranded or solid copper conductor.
- PP PE FR-PE PVC insulation
- PUR jacket
- Tinned or bare copper wire spiral or braid shield
- Rated temperature: 80°C, Rated voltage: 30Volts
- Pass UL VW-1&CUL FT2 vertical flame test

Applications

- For external wiring of systems equipment and electronic equipment.

Technical Data

UL Style & CSA Type	Cores	Conductor		Insulation Thickness	Nom. Dia	Shield Coverage	Jacket Thickness	Overall Diameter	Conductor Resistance at 20°C
		Gauge	No./OD						
		AWG	No./mm						
UL20236CUL (Stranded)	2C	30	7/0.100	0.23	0.80	≥65	0.76	3.70	381.00
		28	7/0.127	0.23	0.90	≥65	0.76	4.00	239.00
		26	7/0.16	0.23	1.00	≥65	0.76	4.20	150.00
		24	11/0.16	0.23	1.10	≥65	0.76	4.40	94.20
		22	17/0.16	0.23	1.30	≥65	0.76	4.70	59.40
		20	21/0.178	0.23	1.50	≥65	0.76	5.20	36.70
		18	34/0.178	0.23	1.80	≥65	0.76	5.80	23.20
UL20236CUL (Stranded)	3C	30	7/0.100	0.23	0.80	≥65	0.76	3.80	381.00
		28	7/0.127	0.23	0.90	≥65	0.76	4.00	239.00
		26	7/0.16	0.23	1.00	≥65	0.76	4.20	150.00
		24	11/0.16	0.23	1.10	≥65	0.76	4.50	94.20
		22	17/0.16	0.23	1.30	≥65	0.76	4.90	59.40
		20	21/0.178	0.23	1.50	≥65	0.76	5.40	36.70
		18	34/0.178	0.23	1.80	≥65	0.76	6.00	23.20
UL20236CUL (Stranded)	4C	30	7/0.100	0.23	0.80	≥65	0.76	4.00	381.00
		28	7/0.127	0.23	0.90	≥65	0.76	4.30	239.00
		26	7/0.16	0.23	1.00	≥65	0.76	4.50	150.00
		24	11/0.16	0.23	1.10	≥65	0.76	4.80	94.20
		22	17/0.16	0.23	1.30	≥65	0.76	5.30	59.40
		20	21/0.178	0.23	1.50	≥65	0.76	5.60	36.70
		18	34/0.178	0.23	1.80	≥65	0.76	6.00	23.20
UL20236CUL (Stranded)	5C	30	7/0.100	0.23	0.80	≥65	0.76	4.30	381.00
		28	7/0.127	0.23	0.90	≥65	0.76	4.50	239.00
		26	7/0.16	0.23	1.00	≥65	0.76	4.80	150.00
		24	11/0.16	0.23	1.10	≥65	0.76	5.00	94.20
UL20236CUL (Stranded)	6C	22	17/0.16	0.23	1.30	≥65	0.76	5.60	59.40
		30	7/0.100	0.23	0.80	≥65	0.76	4.50	381.00
		28	7/0.127	0.23	0.90	≥65	0.76	4.80	239.00
		26	7/0.16	0.23	1.00	≥65	0.76	5.20	150.00
		24	11/0.16	0.23	1.10	≥65	0.76	5.40	94.20

PUR Jacket cable