


M8 B-coding (Devicenet)



M8 B-coding Angled Connector, Molded Cable, Plastic

Female



Specifications

Contacts	5
Pin layout(Female)	
Standard	IEC 61076-2-104
Ambient temperature	-25°C ~ +85°C (flexible installation) , -40°C ~ +85°C (fixed installation)
Connector insert	TPU;PA
Connector contacts	Brass with gold plated
Connector overmold	TPU
Coupling nut/screw	PA+GF
Seal/O-ring(of Female)	FKM
Insulation resistance	≥100MΩ
Contact resistance	≤5mΩ
Shielding	Unavailable
IP rating	IP67 in locked condition
Mating endurance	>500 cycles
Rated current	3 A
Rated voltage	30V AC / DC
Wire gauge	0.25mm² (AWG24)

Part Number

Pins	Cable length	Female	
		PVC	PUR
5	1m	MA08FBP05RA-10CB25	MA08FBP05RA-10RB25
	3m	MA08FBP05RA-30CB25	MA08FBP05RA-30RB25
	5m	MA08FBP05RA-50CB25	MA08FBP05RA-50RB25

Default wire colors

Pin No.	
Pin 1	Shield
Pin 2	DR
Pin 3	WH
Pin 4	BK
Pin 5	BU