


M12 A-coding (Sensor and Actuator)


M12 A-coding Angled Connector, Molded Cable, Shielded

Male



CE RoHS

Female



CE RoHS

Specifications

Contacts	3	4	5	8	12	17
Certification	CYJV2(CYJV8).E321413				CYJV(CYJV7).E321413	
Pin layout(Male)						
Pin layout(Female)						
Standard	IEC 61076-2-101					
Ambient temperature	-25°C ~ +85°C (flexible installation) , -40°C ~ +85°C (fixed installation)					
Connector insert	TPU+GF					
Connector contacts	Brass with gold plated					
Connector overmold	TPU					
Coupling nut/screw	Zinc alloy with nickel plated (12pin,17pin brass with nickel plated)					
Seal/O-ring(of Female)	FKM					
Insulation resistance	≥ 100MΩ					
Contact resistance	≤ 5mΩ					
Shielding	Available					
IP rating	IP67, IP68, IP69K in locked condition					
Mating endurance	>500 cycles					
Rated current	4 A		2A		1.5A	
Rated voltage	250V AC/DC		60V AC/DC		30V AC/DC	
Wire gauge	0.34mm ² (AWG22)		0.25mm ² (AWG24)		0.14mm ² (AWG26)	

Part Number

*12 pin 17 pin with different overmold from above other pins.

Pins	Cable length	Male		Female	
		PVC	PUR	PVC	PUR
3	1m	MA12MSAHD03RA-10CB34	MA12MSAHD03RA-10RB34	MA12FSAHD03RA-10CB34	MA12FSAHD03RA-10RB34
	3m	MA12MSAHD03RA-30CB34	MA12MSAHD03RA-30RB34	MA12FSAHD03RA-30CB34	MA12FSAHD03RA-30RB34
	5m	MA12MSAHD03RA-50CB34	MA12MSAHD03RA-50RB34	MA12FSAHD03RA-50CB34	MA12FSAHD03RA-50RB34
4	1m	MA12MSAHD04RA-10CB34	MA12MSAHD04RA-10RB34	MA12FSAHD04RA-10CB34	MA12FSAHD04RA-10RB34
	3m	MA12MSAHD04RA-30CB34	MA12MSAHD04RA-30RB34	MA12FSAHD04RA-30CB34	MA12FSAHD04RA-30RB34
	5m	MA12MSAHD04RA-50CB34	MA12MSAHD04RA-50RB34	MA12FSAHD04RA-50CB34	MA12FSAHD04RA-50RB34
5	1m	MA12MSAHD05RA-10CB34	MA12MSAHD05RA-10RB34	MA12FSAHD05RA-10CB34	MA12FSAHD05RA-10RB34
	3m	MA12MSAHD05RA-30CB34	MA12MSAHD05RA-30RB34	MA12FSAHD05RA-30CB34	MA12FSAHD05RA-30RB34
	5m	MA12MSAHD05RA-50CB34	MA12MSAHD05RA-50RB34	MA12FSAHD05RA-50CB34	MA12FSAHD05RA-50RB34
8	1m	MA12MSAHD08RA-10CB25	MA12MSAHD08RA-10RB25	MA12FSAHD08RA-10CB25	MA12FSAHD08RA-10RB25
	3m	MA12MSAHD08RA-30CB25	MA12MSAHD08RA-30RB25	MA12FSAHD08RA-30CB25	MA12FSAHD08RA-30RB25
	5m	MA12MSAHD08RA-50CB25	MA12MSAHD08RA-50RB25	MA12FSAHD08RA-50CB25	MA12FSAHD08RA-50RB25
12	1m	MA12MSAF12RA-10CB14	MA12MSAF12RA-10RB14	MA12FSAF12RA-10CB14	MA12FSAF12RA-10RB14
	3m	MA12MSAF12RA-30CB14	MA12MSAF12RA-30RB14	MA12FSAF12RA-30CB14	MA12FSAF12RA-30RB14
	5m	MA12MSAF12RA-50CB14	MA12MSAF12RA-50RB14	MA12FSAF12RA-50CB14	MA12FSAF12RA-50RB14
17	1m	MA12MSAF17RA-10CB14	MA12MSAF17RA-10RB14	MA12FSAF17RA-10CB14	MA12FSAF17RA-10RB14
	3m	MA12MSAF17RA-30CB14	MA12MSAF17RA-30RB14	MA12FSAF17RA-30CB14	MA12FSAF17RA-30RB14
	5m	MA12MSAF17RA-50CB14	MA12MSAF17RA-50RB14	MA12FSAF17RA-50CB14	MA12FSAF17RA-50RB14

Default wire colors

Pin No.						
Pin 1	BN	BN	BN	WH	WH	BN 13. WH/GN
Pin 2		WH	WH	BN	BN	BU 14. BN/GN
Pin 3	BU	BU	BU	GN	GN	WH 15. WH/YE
Pin 4	BK	BK	BK	YE	YE	GN 16. YE/BN
Pin 5			GY	GY	GY	PK 17. WH/GY
Pin 6				PK	PK	YE
Pin 7				BU	BU	BK
Pin 8				RD	RD	GY
Pin 9					OR	RD
Pin 10					TP	VT
Pin 11					BK	GY/PK
Pin 12					VT	RD/BU
Shell	Braid					