


M12 Y3-coding



M12 Y3-coding Straight Connector, Molded Cable, Shielded

Female



Specifications

Contacts	6
Pin layout(Female)	
Standard	IEC 61076-2-113
Ambient temperature	-25°C ~ +85°C (flexible installation) , -40°C ~ +85°C (fixed installation)
Connector insert	TPU+GF
Connector contacts	Brass with gold plated
Connector overmold	TPU
Coupling nut/screw	Brass with nickel plated
Seal/O-ring	FKM
Insulation resistance	≥100MΩ
Contact resistance	≤10mΩ
Shielding	Available
IP rating	IP67 in locked condition
Mating endurance	>500 cycles
Rated current	12 A(Power pins) / 0.5A(Data pins)
Rated voltage	50V AC/ DC
Wire gauge	1.25 mm ² (AWG 16)(Power pins)/ 0.15 mm ² (AWG 26)(Data pins)

Part Number

Pins	Cable length	Female	
		PVC	PUR
6	1m	MA12FSY3F06ST-10CB25	MA12FSY3F06ST-10RB25
	3m	MA12FSY3F06ST-30CB25	MA12FSY3F06ST-30RB25
	5m	MA12FSY3F06ST-50CB25	MA12FSY3F06ST-50RB25

Default wire colors

Pin No.	
Pin 1(Data)	WH
Pin 2(Data)	OR
Pin 3(Data)	RD
Pin 4(Data)	GN
Pin 5(Power)	RD
Pin 6(Power)	BK
Shell	Braid

Hybrid