


Mini-change(7/8")




Mini-change(7/8") Straight Connector, Field Assembly, Screw Termination with pilot hole

Male



Female



Specifications

Contacts	3	4	5
Certification	cULus PVVA.E496340		
Pin layout(Male)			
Pin layout(Female)			
Ambient temperature	-40°C ~ +90°C		
Connector insert	TPU		
Connector contacts	Brass with gold plated		
Coupling screw	Zinc alloy with nickel plated		
Connector body	PA+GF		
Seal/O-ring(of Female)	FKM		
Insulation resistance	≥100MΩ		
Contact resistance	≤5mΩ		
Shielding	Unavailable		
Suitable cable Dia	A: 6.0~8.0mm; B: 8.0~10.0mm		
IP rating	IP67, IP68 in locked condition		
Mating endurance	>500 cycles		
Rated current	13A		8A
Rated voltage	300V AC / DC		
Wire gauge	1.5~2.0mm ² (16~14AWG)		

Part Number

Pins	Male		Female	
	A	B	A	B
3	MINI-C03MST-SSF-A	MINI-C03MST-SSF-B	MINI-C03FST-SSF-A	MINI-C03FST-SSF-B
4	MINI-C04MST-SSF-A	MINI-C04MST-SSF-B	MINI-C04FST-SSF-A	MINI-C04FST-SSF-B
5	MINI-C05MST-SSF-A	MINI-C05MST-SSF-B	MINI-C05FST-SSF-A	MINI-C05FST-SSF-B

Assembly Instruction

