


FSA Fixed Straight Socket, 250 Coaxial, Rear Fastened

- Connector series: FSA
 - Contact: Female
 - Locking type: Self-locking
 - Orientation type: Straight
 - Part No.: FSA.1E.250.CTL
 - Mated with: PSA.1E.250.CLACxx(Z)
- Note: "X" refers to part number definition on page 101




General information

Ambient temperature:	-55°C~+200°C
Endurance:	>5000 cycles
Insulator:	PTFE
Connector contacts:	Brass with gold plated
Housing:	Brass with Cr plated
Impedance:	50Ω

Rated current:	12A
VSWR:	1.01+0.23*f/GHz
Insulator resistance:	≥100MΩ
IP rating:	IP 68
Shielding efficiency:	at 10MHz>95dB/at 1GHz>80dB
Salt spray corrosion test:	>144h

FSA Fixed Straight Socket, Coaxial Triaxial, Rear Fastened

- Connector series: FSA
 - Contact: Female
 - Locking type: Self-locking
 - Orientation type: Straight
 - Part No.: FSA.1E.650.CTL
 - Mated with: PSA.1E.650.CLACxx(Z)
- Note: "X" refers to part number definition on page 101



General information

Ambient temperature:	-55°C~+200°C
Endurance:	>5000 cycles
Insulator:	PTFE
Connector contacts:	Brass with gold plated
Housing:	Brass with Cr plated
Impedance:	50Ω

Rated current:	6A
VSWR:	1.01+0.17*f/GHz
Insulator resistance:	≥100MΩ
IP rating:	IP 68
Shielding efficiency:	at 10MHz>95dB/at 1GHz>80dB
Salt spray corrosion test:	>144h