

■ PSN Straight Plug, Cable Collet(Two Keys)

• Connector series: PSN

• Contact: Male

Locking type: Self-locking
Orientation type: Straight
Part No.: PSN.0R.XXX.KLACXXZ
Mated with: FRN.0R.XXX.KLL



Note: "X" refers to part number definition on page 126

■ General Information

Ambient temperature:	-20°C ~ + 80°C
Endurance:	≥3000 cycles
Insulator:	PEEK
Connector contacts:	Brass with gold plated
Coupling nut/screw:	Brass with black Cr plated

Housing:	Brass with black Cr plated
Insulator resistance:	≥100MΩ
IP rating:	IP 68
Shielding effciency:	at 10MHz>75dB/at 1GHz>40dB
Salt spray corrosion test:	>144h

■ FRN Fixed Socket With Earthing Tag, Front Fasten (Two Keys)


• Connector series: FRN

• Contact: Female

Locking type: Self-lockingOrientation type: StraightPart No.: FRN.0R.XXX.KLL

• Mated with: PSN.0R.XXX.KLACXXZ

Note: "X" refers to part number definition on page 126





■ General Information

Ambient temperature:	-20°C ~ + 80°C
Endurance:	≥3000 cycles
Insulator:	PEEK
Connector contacts:	Brass with gold plated
Coupling nut/screw:	Brass with black Cr plated

Note: Panel cut-out (page 164)

Housing:	Brass with black Cr plated
Insulator resistance:	≥100MΩ
IP rating:	IP 68
Shielding effciency:	at 10MHz>75dB/at 1GHz>40dB
Salt spray corrosion test:	>144h

FINECABLES ENTERPRISE CO., LIMITED www.finecables.com | 129