


■ SRG Fixed Socket, Nut Fixing, Back Panel Mounting

- Connector series: SRG
 - Contact: Female
 - Key: G(More keys, refer to page 77)
 - Locking type: Self-locking
 - Orientation type: Straight
 - Part No.: SRG.xT.3xx.xLL
 - Mated with: PSG
- Note: "X" refers to part number definition on page 70



■ General Information

Ambient temperature:	-55°C ~ + 200°C
Endurance:	>3000 cycles
Insulator:	PEEK
Connector contacts:	Brass with gold plated
Housing:	Brass with Cr plated

O-Ring:	Silicone
Insulator resistance:	≥100MΩ
IP rating:	IP 68
Shielding efficiency:	at 10MHz>75dB/at 1GHz>40dB
Salt spray corrosion test:	>144h

Size	Dimensions(mm)							
	A	B	e	E	L	N	P	S1
TT	10.0	10.0	M7*0.5	4.5	16.0	13.5	7	6.3
0T	12.0	12.0	M9*0.6	6.5	21.0	19.1	9	8.2
1T	15.5	16.0	M12*1.0	6.5	23.0	21.5	10	10.5
2T	18.5	20.0	M15*1.0	7.5	26.5	24.6	11	13.5
3T	23.5	24.0	M18*1.0	7.5	30.1	25.0	12	16.5

Panel cut out(page 164)