

■ Cable Assembly Cable Stripping Lengths

■ B series

Series	Pin Count(P/N)	Straight Socket and Plug						90 Right Angled Socket					
		Solder Contacts			Crimp Contacts			Solder Contacts			Crimp Contacts		
		L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)
00	302/303/304	7.0	4	2.5	10.0	4	3.0	9.5	4	2.5	12.5	4	3.0
0B ¹⁾	302/303	13.0	7	3.0	17.0	7	4.0	18.0	7	3.0	22.0	7	4.0
	304/305	13.0	7	3.0	17.0	7	4.0	18.0	7	3.0	22.0	7	4.0
	306/307/309	12.5	7	2.5	18.0	7	3.0	19.0	7	2.5	23.0	7	3.0
1B ¹⁾	302/303	14.0	8	3.5	18.0	8	4.0	25.0	8	3.5	28.0	8	4.0
	304/305	14.0	8	3.0	18.0	8	4.0	25.0	8	3.0	28.0	8	4.0
	306/307/308	14.0	8	3.0	18.0	8	4.0	25.0	8	3.0	28.0	8	4.0
	310/314/316	13.5	8	2.5	-	-	-	27.5	8	2.5	-	-	-
2B	302	16.0	9	4.0	22.0	9	5.5	30.0	9	4.0	33.0	9	5.5
	303	16.0	9	3.5	22.0	9	5.5	30.0	9	3.5	33.0	9	5.5
	304/305/306/307	16.0	9	3.5	20.0	9	4.0	29.0	9	3.5	31.0	9	4.0
	308/310	15.0	9	3.0	20.0	9	4.0	28.0	9	3.0	31.0	9	4.0
	312/314/316/318/319	15.0	9	3.0	20.0	9	4.0	28.0	9	3.0	31.0	9	4.0
	326/332	15.0	9	2.5	-	-	-	28.0	9	2.5	-	-	-
3B	302	24.0	10	4.5	28.0	10	5.5	35.0	10	4.5	39.0	10	5.5
	303/304	23.0	10	4.0	27.0	10	5.5	34.0	10	4.0	38.0	10	5.5
	305/306/307	23.0	10	3.5	27.0	10	5.5	34.0	10	3.5	38.0	10	5.5
	308/310	22.0	10	3.5	25.0	10	4.0	33.0	10	3.5	36.0	10	4.0
	309	22.0	10	3.5 4.0	25.0	10	4.0 5.5	33.0	10	3.5 4.0	36.0	10	4.0 5.5
	312/314/316/318	21.0	10	3.0	25.0	10	4.0	32.0	10	3.0	36.0	10	4.0
	320/322/324/326/330	21.0	10	3.0	25.0	10	4.0	32.0	10	3.0	36.0	10	4.0
4B	304	33.0	12	4.5	36.0	12	5.5	41.0	12	4.5	45.0	12	5.5
	306/307	32.0	12	4.0	36.0	12	5.5	41.0	12	4.0	45.0	12	5.5
	310	32.0	12	3.5	36.0	12	5.5	39.0	12	3.5	43.0	12	5.5
	312	32.0	12	3.5	36.0	12	4.0	39.0	12	3.5	43.0	12	4.0
	316/320/324/330	32.0	12	3.0	34.0	12	4.0	39.0	12	3.0	43.0	12	4.0
	340/348	32.0	12	3.0	34.0	12	4.0	39.0	12	3.0	43.0	12	4.0

Note:

- 1) In 0B and 1B series, <L> and <S> dimensions shall be increased by 2mm for largest collet(D56 in 0B series, D76 in 1B series)
- 3) the tolerances on these dimensions are: L:±0.5mm, S:±0.5mm, T±0.2mm
- 2) For the central contacts, the wires shall be reduced by 1.5-2.0mm

■ K series

Series	Pin Count(P/N)	Straight Socket and Plug						90 Right Angled Socket					
		Solder Contacts			Crimp Contacts			Solder Contacts			Crimp Contacts		
		L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)
0K	302/303	9.5	6	3.0	12.0	6	4.0	21.0	6	3.0	25.0	6	4.0
	304/305	9.5	6	3.0	12.0	6	4.0	21.0	6	3.0	25.0	6	4.0
	306/307/309	9.0	6	2.5	13.0	6	4.0	22.0	6	2.5	26.0	6	4.0
1K	302/303	10.5	7	3.5	14.5	7	4.0	27.0	7	3.5	31.0	7	4.0
	304/305	10.5	7	3.0	14.5	7	4.0	27.0	7	3.0	31.0	7	4.0
	306/307/308	10.5	7	3.0	14.5	7	4.0	27.0	7	3.0	31.0	7	4.0
	310/314/316	13.0	7	2.5	-	-	-	29.5	7	2.5	-	-	-