

■ Cable Assembly Cable Stripping Lengths

■ K series

Series	Pin Count(P/N)	Straight Socket and Plug						90 Right Angled Socket					
		Solder Contacts			Crimp Contacts			Solder Contacts			Crimp Contacts		
		L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)
2K	302	16.5	8	4.0	19.5	8	5.5	36.0	8	4.0	39.0	8	5.5
	303	16.5	8	3.5	19.5	8	5.5	36.0	8	3.5	39.0	8	5.5
	304/305/306/307	15.5	8	3.5	17.5	8	4.0	35.0	8	3.5	37.0	8	4.0
	308/310	14.5	8	3.0	17.5	8	4.0	34.0	8	3.0	37.0	8	4.0
	312/314/316/318/319	14.5	8	3.0	17.5	8	4.0	34.0	8	3.0	37.0	8	4.0
	326/332	14.5	8	2.5	-	-	-	34.0	8	2.5	-	-	-
3K	302	19.0	10	4.5	23.0	10	5.5	48.0	10	4.5	53.0	10	5.5
	303/304	18.0	10	4.0	22.0	10	5.5	48.0	10	4.0	52.0	10	5.5
	305/306/307	18.0	10	3.5	22.0	10	5.5	48.0	10	3.5	52.0	10	5.5
	308/310	17.0	10	3.5	20.0	10	4.0	47.0	10	3.5	50.0	10	4.0
	309	17.0	10	3.5 4.0	20.0	10	4.0 5.5	47.0	10	3.5 4.0	50.0	10	4.0 5.5
	312/314/316/318	16.0	10	3.0	20.0	10	4.0	46.0	10	3.0	50.0	10	4.0
	320/322/324/326/330	16.0	10	3.0	20.0	10	4.0	46.0	10	3.0	50.0	10	4.0
4K	304	22.0	11	4.5	25.0	11	5.5	52.0	11	4.5	55.0	11	5.5
	306/307	21.0	11	4.0	25.0	11	5.5	51.0	11	4.0	55.0	11	5.5
	310	21.0	11	3.5	25.0	11	5.5	51.0	11	3.5	55.0	11	5.5
	312	21.0	11	3.5	25.0	11	4.0	51.0	11	3.5	55.0	11	4.0
	316/320/324/330	21.0	11	3.0	23.0	11	4.0	51.0	11	3.0	53.0	11	4.0
	340/348	21.0	11	3.0	23.0	11	4.0	51.0	11	3.0	53.0	11	4.0



Note:
For the central contacts, the wires shall be reduced by 1.5~2.5mm
The tolerance:
L:±0.5mm; S:±0.5mm; T:±0.2mm.

■ K Series (Stright plug and stright socket with oversize cable collet)

Series	Pin Count(P/N)	90 Right Angled Socket					
		Solder Contacts			Crimp Contacts		
		L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)
1K	302/303	23.5	8	3.5	27.5	8	4.0
	304/305	23.5	8	3.0	27.5	8	4.0
	306/307/308	23.5	8	3.0	27.5	8	4.0
	310/314/316	24.5	8	2.5	-	-	-
2K		29.5	10	4.0	32.5	10	5.5
		29.5	10	3.5	32.5	10	5.5
	304/305/306/307	28.5	10	3.5	30.5	10	4.0
	308/310	27.5	10	3.0	30.5	10	4.0
	312/314/316/318/319	27.5	10	3.0	30.5	10	4.0
	326/332	27.5	10	2.5	-	-	-
3K	302	37.0	11	4.5	41.0	11	5.5
	303/304	36.0	11	4.0	40.0	11	5.5
	305/306/307	36.0	11	3.5	40.0	11	5.5
	308/310	35.0	11	3.5	38.0	11	4.0
	309	34.0	11	3.0	38.0	11	4.0 5.5
	312/314/316/318	34.0	11	3.0	38.0	11	4.0
	320/322/324/326/330	34.0	11	3.0	38.0	11	4.0