

■ Cable Assembly Cable Stripping Lengths

■ K Series (Stright plug and stright socket with oversize cable collet)

Series	Pin Count(P/N)	90 Right Angled Socket					
		Solder Contacts			Crimp Contacts		
		L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)
4K	306/307	44.0	14	4.0	48.0	14	5.5
	310	44.0	14	3.5	48.0	14	5.5
	312	44.0	14	3.5	48.0	14	4.0
	316/320/324/330	44.0	14	3.0	46.0	14	4.0
	340/348	44.0	14	3.0	46.0	14	4.0

Note:
For the central contacts, the wires shall be reduced by 1.5~2.5mm
The tolerance:
L:±0.5mm; S:±0.5mm; T:±0.2mm.

■ T series

Series	Pin Count(P/N)	Solder Contacts			Crimp Contacts		
		L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)
TT	302/303/304	7.0	4.0	2.5	10.0	4.0	3.0
	305/306	7.0	4.0	2.5	-	-	-
OT	302/303	9.5	6.0	3.5	12.0	6.0	4.0
	304/305	9.5	6.0	3.5	12.0	6.0	4.0
	1) 306/307/309	9.0	6.0	2.5	13.0	6.0	3.0
	312	9.0	6.0	2.5	-	-	-
1T	302/303	11.0	7	3.5	14.5	7	4.0
	304/305	11.0	7	3.0	14.5	7	4.0
	306/307/308	11.0	7	3.0	14.5	7	4.0
	310/314/316	13.0	7	2.5	-	-	-
3T	302	16.5	8	4.0	19.5	8	5.5
	303	16.5	8	3.5	19.5	8	5.5
	304/305/306/307	15.5	8	3.5	17.5	8	4.0
	308/310	14.5	8	3.0	17.5	8	4.0
	312/314/316/318/319	14.5	8	3.0	17.5	8	4.0
	326/332	14.5	8	2.5	-	-	-

Note:
1) Crimp contacts are available only for connectors fitted with male contacts
2) The tolerances on these dimensions are. L:±0.5mm; S:±0.5mm; T:±0.2mm