

■ Cable Assembly Cable Stripping Lengths

■ S series

Series	Pin Count(P/N)	Straight Socket and Plug						90 Right Angled Socket					
		Solder Contacts			Crimp Contacts			Solder Contacts			Crimp Contacts		
		L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)	L(mm)	S(mm)	T(mm)
0S	302	10	5	4.0	15	5	4.0	10	5	4.0	15	5	4.0
	303/304	10	5	4.0	15	5	4.0	10	5	4.0	15	5	4.0
1S	302	13	8	3.0	17	8	4.0	13	8	3.0	17	8	4.0
	303/304	13	8	3.0	17	8	4.0	13	8	3.0	17	8	4.0
	305	13	8	3.0	17	8	4.0	13	8	3.0	17	8	4.0
		13	8	2.5	17	8	4.0	13	8	2.5	17	8	4.0
306	13	8	2.5	17	8	4.0	13	8	2.5	17	8	4.0	
2S	302	18	9	4.5	22	9	5.5	18	9	4.5	22	9	5.5
	303/304/305/306	18	9	4.0	22	9	4.0	18	9	4.0	22	9	4.0
	307	18	9	4.0	22	9	4.0	18	9	4.0	22	9	4.0
		18	9	4.0	22	9	4.0	18	9	4.0	22	9	4.0
308/310	18	9	4.0	22	9	4.0	18	9	4.0	22	9	4.0	

■ E series

Series	Pin Count(P/N)	Solder Contacts		
		L(mm)	S(mm)	T(mm)
0E	302	9.0	4.0	3.5
	303/304	9.0	4.0	3.5
1E	302	10.5	6.0	3.5
	303/304	10.5	6.0	3.0
	305	10.5	6.0	3.0
	306	10.5	6.0	3.0
2E	302	14.0	9.0	3.5
	303/304/305/306	14.5	9.0	3.5
	307	14.5	9.0	3.5/3.0
	308/310	14.0	9.0	3.0



Note:
1) The tolerances on these dimensions are. L: ±0.5mm; S: ±0.5mm; T: ±0.2mm

■ L series

Series	Pin Count(P/N)	Solder Contacts		
		L(mm)	S(mm)	T(mm)
0L	302	11.0	6.0	3.5
	303/304	11.5	6.0	3.5
1L	302	13.0	7.0	3.5
	303/304	12.5	7.0	3.0
	305	12.5	7.0	3.0
	306	13.0	7.0	3.0
2L	302	17.0	8.0	3.5
	303/304/305/306	16.5	8.0	3.5
	307	16.5/15.0	8.0	3.5/3.0
	308/310	15.0	8.0	3.0



Note:
1) The tolerances on these dimensions are. L: ±0.5mm; S: ±0.5mm; T: ±0.2mm