


M12 M-coding (Power)



M12 M-coding Straight Connector, Panel Mount, Solder&Crimp, Rear fastened



Specifications

Contacts	6 (5+PE)
Pin layout(Male)	
Pin layout(Female)	
Standard	IEC 61076-2-111
Ambient temperature	-20°C~ + 80°C(flexible installation)/-40°C~ + 80°C(fixed installation)
Connector insert	PA + GF
Connector contacts	Brass with nickel plated
Connector overmold	TPU
Coupling nut/screw:	Brass with nickel plated
Seal / O-ring	FKM
Insulation resistance	≥100MΩ
Contact resistance	≤5mΩ
Shielding	Unavailable
IP rating	IP67, IP68 in locked condition
Rated current	8 A
Rated voltage	630V AC/DC
Wire gauge	1.5mm² (AWG16)
Panel cut-out	Refer to page 416

Part Number

Pins	Cable length	Connection Type	公头		母头	
			M16x1.5	PG9	M16x1.5	PG9
6	0.1m	Solder	MB12MSMRF06ST-215001	MB12MSMRF06ST-315001	MB12FSMRF06ST-215001	MB12FSMRF06ST-315001
	0.3m		MB12MSMRF06ST-215003	MB12MSMRF06ST-315003	MB12FSMRF06ST-215003	MB12FSMRF06ST-315003
	0.1m	Crimp	MB12MCMRF06ST-215001	MB12MCMRF06ST-315001	MB12FCMRF06ST-215001	MB12FCMRF06ST-315001
	0.3m		MB12MCMRF06ST-215003	MB12MCMRF06ST-315003	MB12FCMRF06ST-215003	MB12FCMRF06ST-315003

Default wire colors

Pin No.	
Pin 1	BN
Pin 2	WH
Pin 3	BU
Pin 4	BK
Pin 5	GY
Pin 6	YE/GN