


M12 B-coding (Profibus)




M12 B-coding Angled Connector, Field Wirable Assembly, Screw joint, Die-cast Screw/Nut

Male



Female



Specifications

Contacts	3	4	5
Certification	CYJV(CYJV7).E321413		
Pin layout(Male)			
Pin layout(Female)			
Standard	IEC 61076-2-101		
Ambient temperature	-25°C~+90°C		
Connector insert	TPU		
Connector contacts	Brass with gold plated		
Connector body	PA+GF		
Coupling nut/screw	Zinc alloy with nickel plated		
Seal/O-ring	NBR		
Insulation resistance	≥100MΩ		
Contact resistance	≤5mΩ		
Shielding	Unavailable		
Suitable cable Dia	PG7: 4~6mm / PG9: 6~8mm		
IP rating	IP67, IP68 in locked condition		
Mating endurance	>500 cycles		
Rated current	4 A		
Rated voltage	250V AC/DC		60V AC/DC
Wire gauge	0.34mm ² (AWG22)		

Part Number

Pins	Male		Female	
	PG9	PG7	PG9	PG7
3	MB12MWBHD03RA-3	MB12MWBHD03RA-4	MB12FWBHD03RA-3	MB12FWBHD03RA-4
4	MB12MWBHD04RA-3	MB12MWBHD04RA-4	MB12FWBHD04RA-3	MB12FWBHD04RA-4
5	MB12MWBHD05RA-3	MB12MWBHD05RA-4	MB12FWBHD05RA-3	MB12FWBHD05RA-4

Assembly Instruction

